

Applicant : Klaus-Dieter Pillekamp et al.
Serial No. : 09/787,868
Filed : March 22, 2001
Page : 8

Attorney's Docket No.: 12758-
025001 / 1998P02638WOUS

REMARKS

Applicants have amended the application to cancel claims 1-31 and have added claims 32-63. Please consider these newly added claims prior to examination. Applicants have also replaced the abstract. No new matter has been added.

Attached is a marked-up version of the changes being made by the current amendment.

Applicant asks that all claims be examined. Enclosed is a \$186.00 check for ~~excess claim~~ fees. Please apply any other charges or credits to Deposit Account No. 06-1050.

Respectfully submitted,

Date: December 28, 2001

Ellen Sein Aye
Ellen Sein Aye
Reg. No. 42,729

Fish & Richardson P.C.
225 Franklin Street
Boston, Massachusetts 02110-2804
Telephone: (617) 542-5070
Facsimile: (617) 542-8906

Version with markings to show changes made

In the claims:

Claims 1-31 have been cancelled.

Claims 32-63 have been added as follows:

--32. (New) A terminal comprising:

a transmitter stage;

a receiver stage;

a switch-over and adapter stage having an arrangement of passive structural elements connected to a plurality of microswitches or microrelays programmed by a predetermined configuration in at least one functional parameter; and

a control unit associated with the transmitter stage and the receiver stage, for setting predetermined values of the functional parameter.

33. (New) The terminal of claim 32 wherein the functional parameter is a frequency characteristic.

34. (New) The terminal of claim 32 wherein at least one of the transmitter stage, receiver stage, and switch-over, or adapter stage includes a plurality of micromotors having a control connection to the control unit for mechanically adjusting the passive structural elements.

35. (New) The terminal of claim 32 wherein the control unit has an on/off switch for the transmitter stage and the receiver stage, and a switch-off signal is transmitted to the on/off switch before an actuation signal is transmitted to the microswitch or microrelay configuration to deactivate the transmitter stage and the receiver stage.

36. (New) The terminal of claim 35 wherein the control unit has a sensing unit connected to the on/off switch for transmitting a switch-on signal to the on/off switch to activate

the transmitter and the receiver stage after termination of a program run for setting the functional parameter.

37. (New) The terminal of claim 32 wherein the plurality of microswitches or microrelays are integrated with the passive structural elements on a substrate with a high dielectric constant.

38. (New) The terminal of claim 34 wherein at least one of the plurality of micromotors is integrated with the passive structural elements on a substrate with a high dielectric constant.

39. (New) The terminal of claim 32 wherein the control unit includes:
a topology memory for storing a topology of the arrangement of passive structural elements, the topology including the plurality of microswitches or microrelays and configured to determine the functional parameter;
an algorithm memory for storing a calculation algorithm for a predetermined value of the functional parameter based on the topology; and
a calculation stage for determining the configuration to be actuated to implement the predetermined value, based on the stored calculation algorithm.

40. (New) The terminal of claim 39 wherein the topology memory is configured to store a position and a topology corresponding to actuator stages of a micromotor, and the calculation stage is configured to calculate an actuation signal for the micromotor, the signal being output to implement a predetermined value of the functional parameter.

41. (New) The terminal of claim 32 wherein the control unit includes:
a configuration memory for storing a plurality of switched setting configurations of the microswitches or microrelays, in an assignment to a value of the functional parameter or a values vector of the functional parameter; and

a pointer stage for addressing the configuration memory as a function of the value or the values vector.

42. (New) The terminal of claim 41 wherein the configuration memory is configured to store a combined switch setting and motor actuation configurations of the arrangement of passive structural elements.

43. (New) A method for operating a terminal, said terminal comprising:
transmitting an actuation signal from a transmitter stage to a receiver stage; and
deactivating the transmitter stage and the receiver stage before the actuation
signal is transmitted to a microswitch configuration, a microrelay configuration, or a
micromotor.

44. (New) The method of claim 43 further comprising automatically reactivating the
transmitter stage and the receiver stage after a program run for setting a functional parameter is
terminated.

45. (New) The method of claim 43 further comprising:
determining a topology memory for storing a topology of the arrangement of
passive structural elements, the topology including the plurality of microswitches or microrelays
and configured to determine the functional parameter;

determining an algorithm memory for storing a calculation algorithm for a
predetermined value of the functional parameter based on the topology; and
determining a calculation stage for identifying, based on the stored calculation
algorithm, the configuration to be actuated to implement the predetermined value.

46. (New) The method of claim 45 wherein the topology memory stores a position
and a topology corresponding to actuator stages of a micromotor, the calculation stage calculates
an actuation signal for the micromotor, and the signal implements a predetermined value of the
functional parameter.

47. (New) A programmable RF block for phone applications, said block comprising:
an active component;
at least one tunable adapter network having an adjustable passive component, the
adapter network being connected to the active component; and
a control unit configured to set the tunable adapter network and configured to
predetermine properties of the RF block relating to a signal response.

48. (New) The programmable RF block of claim 47 wherein the adjustable passive
component includes a micromotor, and the programmable control unit is configured to actuate
the micromotor for setting the tunable adapter network.

49. (New) The programmable RF block of claim 48 wherein the micromotor is
configured to be activated during a period of adjustment for the tunable adapter network.

50. (New) The programmable RF block of claim 48 wherein the memory is connected
to the control unit where setting values for the tunable adapter network or predetermined
properties of the programmable RF block relating to signal response characteristics are stored.

51. (New) The programmable RF block of claim 50 further comprising a table
representing the setting values for achieving the signal response characteristic of the
programmable RF block.

52. (New) The programmable RF block of claim 48 wherein the control unit is
configured to set the programmable RF block with respect to its properties relating to the
operating frequency, bandwidth, amplification power, and noise characteristics.

53. (New) The programmable RF block of claim 50 wherein the control unit is
configured to calculate the setting values, for determining the signal response characteristic of
the programmable RF block for the tunable adapter network.

54. (New) The programmable RF block of claim 48 wherein the control unit is configured to be programmed over an air interface.

55. (New) A mobile phone configured to be programmed over an air interface, the mobile phone comprising:

a programmable RF block for phone applications, said block including:

an active component;

at least one tunable adapter network having an adjustable passive component, the adapter network being connected to the active component; and

a control unit configured to set the tunable adapter network and configured to predetermine properties of the RF block relating to a signal response.

56. (New) A programmable filter circuit for mobile phone applications, the filter circuit comprising:

a plurality of passive components having characteristic values that are adjustable;

an electric micromotor for adjusting the plurality of passive components; and

a control unit for actuating the electric micromotor and for causing the filter circuit to have a characteristic curve.

57. (New) The filter circuit of claim 56 wherein the control unit is connected to a memory configured to store setting values of the plurality of passive components, actuation values for the electric micromotor, and the characteristic curve of the filter circuit.

58. (New) The filter circuit of claim 56 wherein the control unit is configured to calculate the actuation values for the electric micromotor to be transmitted for achieving the characteristic curve of the filter circuit.

59. (New) The filter circuit of claim 58 wherein the plurality of passive components are capacitors having mechanically adjustable capacitance and constructed with a high dielectric constant using ceramic technology.

60. (New) The filter circuit of claim 59 wherein the capacitors have rotatable or slidable metal plates.

61. (New) The filter circuit of claim 56 wherein the plurality of passive components are resonators and the electric micromotor is configured to change the position of a short-circuit conductor with respect to a grounding point to adjust characteristic values of the resonators.

62. (New) The filter circuit of claim 61 wherein the electric micromotor is electrically powered during a period where a corresponding passive component is mechanically adjusted.

63. (New) A programmable duplexer for mobile phone applications comprising:
a plurality of programmable filter circuits including:
a plurality of passive components having characteristic values that are
adjustable;
an electric micromotor for adjusting the plurality of passive components;
and
a control unit for actuating the electric micromotor and for causing the
filter circuit to have a characteristic curve. --

In the abstract:

Replace the abstract with the following version:

-- A programmable mobile phone terminal includes a transmitter stage, a receiver stage, a switch-over and adapter stage having an arrangement of passive structural elements connected to a plurality of microswitches or microrelays programmed by a predetermined configuration in at least one functional parameter, and a control unit associated with the transmitter stage and the receiver stage, for setting predetermined values of the functional parameter. --